

IVECO

**P 220 BK**

**IVECO DAILY 35S14**

CONTRACT NUMBER: 11221381

**NEW**

**AVAILABLE NOW**



## SPECIFICATION

P 220 BK - Palfinger Access Platform

- Working height ca. 22.0 m
- Cage floor height ca. 20.00 m
- Maximum outreach ca. 16.90 m
- Maximum cage load 300 kg
- Swivel range turntable ca. 500°
- Swivel range cage boom ca. 185°
- Swivel range of cage ca. +/- 85°
- Permissible inclination max. 5°
- Outreach reduction with inclination from 0.5°
- swivelling within mirror width
- robust extrusion-moulded aluminium telescope sections with big wall thickness and low weight ensure high stiffness and stability
- coverings made of aluminum
- stabiliser operation from inside of the cage and at the base
- permanent monitoring of inclination and ground clearance of all tyres

## OFFER INFORMATION

Location details

Löbau, 02708 - Germany 

Dealer Name

Palfinger Platforms GmbH

Product type

New

Contract number

11221381

Dealer E-mail

[sales.platforms@palfinger.com](mailto:sales.platforms@palfinger.com)

Dealer phone

**004935854796121**

- operating without stabilisers is possible
- modern modular cage control panel with robust cover
- main movements can be carried out variably via two joysticks, up to four movements simultaneously
- easy-to-clean membrane buttons
- indication of the operating status via durable LEDs
- Home function access from cage control panel and base
- infinite speed adjustment
- automatic cage assistant function
- electro-hydraulic cage levelling
- hydraulic cage rotation with automatic detection of middle position
- flat base below the workman Cage
- anti-crushing protection integrated in the knee bar
- cleaning hatch at cage
- self-closing door for upright entrance to the cage
- 2 anchor points for safety harnesses
- Chassis battery voltage monitoring
- PALDiag for system analysis, integrated in platforms software
- provided user manual and inspection log book
- CE-sign
- multistage approval according to 2007/46/EG incl. Certificate of conformity

\*Abovementioned values are standard values and vary depending on options and chassis

PRODUCT

|                     |           |                       |                      |
|---------------------|-----------|-----------------------|----------------------|
| Manufacturer        | Palfinger | Turret rotation       | 500°                 |
| Model               | P 220 BK  | Basket size           | 1,40 x 0,70 x 1,10 m |
| Construction year   | 2026      | Basket capacity       | 300 kg               |
| Outreach            | 16,90 m   | Basket turning device | +/- 90°              |
| Max. height of work | 22,00 m   | Basket arm angle      | 185°                 |
|                     |           | Basket material       | Aluminium            |

TRUCK

|                    |           |                      |                 |
|--------------------|-----------|----------------------|-----------------|
| Truck manufacturer | Iveco     | Power                | 100 kW (136 PS) |
| Construction year  | NEU - NEW | Emmission standard   | Euro 6e         |
| Wheel base         | 3750 mm   | Gross vehicle weight | 3.500 Kg        |