

SCANIA

PK 1050 TEC

R 560 B8X4NB

CONTRACT NUMBER: PALDRIVE 709

NEW

ON REQUEST



## SPECIFICATION

All images are from a reference project



## PK 1050 TEC

|                             |           |
|-----------------------------|-----------|
| Lifting moment              | 95 mt     |
| Max. outreach incl. fly-jib | 32,4 m    |
| Lifting capacity            | 30.000 Kg |
| Swivel range                | endless   |
| Rope winch type             | 3,5 to    |



## MCC-INSTALLATION

**low built platform**

|                         |                      |
|-------------------------|----------------------|
| Platform length         | 4.800 mm             |
| Platform width          | 2.480 mm             |
| Frontwall height        | 1.400 mm             |
| Side- & rearwall height | 400 mm               |
| Loading height          | 1.180 mm             |
| Platform floor          | plywood, impregnated |

## OFFER INFORMATION

Location details

MCC-NORTH SOLEC, 86-050 - Poland 

Dealer Name

Palfinger EMEA GmbH

PALFINGER

Availability

On request

Product type

New

Contract number

Paldrive 709

Dealer E-mail

sales@palfinger.com

Dealer phone

004366488345792



SCANIA R 560 B8X4NB

|                |                        |
|----------------|------------------------|
| Power          | 560 HP                 |
| Gearbox        | G33CM + Opticruise     |
| Wheelbase      | 1.990/ 2.960/ 1.350 mm |
| Cabin          | CR20N                  |
| GSR II options | included               |

PRODUCT

|              |             |                          |                   |
|--------------|-------------|--------------------------|-------------------|
| Manufacturer | Palfinger   | Construction year        | 2026              |
| Model        | PK 1050 TEC | Lifting moment           | 95 mt             |
|              |             | Outreach / Lifting power | 32,4 m / 1.280 Kg |

TRUCK

|                    |        |                      |                  |
|--------------------|--------|----------------------|------------------|
| Truck manufacturer | Scania | Axes                 | 8x4              |
| Drivers cabine     | CR20N  | Gross vehicle weight | 32.000 kg        |
| Emmission standard | EURO 6 | Construction         | Heavy duty crane |

## PK 1050 TEC

### HYDRAULIC & TECHNICS

- 8 hydraulic boom extensions (G)
- High-speed boom extension system with return oil recovery
- Swivel range endless
- Hydraulic support leg extension (max.support width 8.800mm)
- Support legs can be swiveled hydraulically through 180°
- Additional hydraulic support stabilizers
- Hose equipment for two additional devices including quick coupling (multi-faster)
- 3,5to cable winch on the main arm (hydr. foldable)
- Rope length: 90m

### ASSISTANCE SYSTEMS

- Paltronic 180
- HPSC + LOAD
- Remote controlled stabilizers
- CPS (cabin protection)
- FPS (Frame Protection System)
- P-FOLD (Folding Assistant)
- Weigh function
- AOS (Active Oscillation Suppression)
- SRC (Synchronised Rope Control)
- RTC (Rope Tension Control)

### EQUIPMENT

- Palfinger P6 radio remote control /8 functions with linear levers
- LED - working lights on the articulated arm
- 11,5to & 18,0to load hook
- 2 strand rope equipment on the Crane
- MFA-L (multifunctional adapter)

## PJ 190

### CONFIGURATION

- 6 hydraulic extensions (E)
- High-speed extension system with return oil recovery
- Hydr. tiltable upwards by 25°
- MFA-L - Multifunctional adapter
- 1-stranded rope equipment for the PJ 150
- incl. premium working light



- Painting RAL3020
- hydraulic oil tank 400 l

## INSTALLATION



- Palfinger MCC low build platform
- Platform inner dimensions: 4.800 mm x 2.480 mm
- Front wall: height 1.400 mm
- Side- and rearwalls height: 400 mm
- Platform floor 27 mm plywood, impregnated and sealed
- Various lashing options on the platform floor
- Loading height: 1.180 mm
- 1 pair of Container locks
- 6 working lights
- 2 reversing lights
- Rear view camera
- Two-part telescopic ladder
- Trailer coupling: RF40 G 150 A
- 2 wheel chocks

## SCANIA R 560 B8X4NB

- Engine: 560 Hp, torque max. 2.800 Nm
- Gearbox: G33CM + Opticruise + retarder
- Axle distance: 1.990mm 2.960mm + 1.350mm
- air suspension on all axles
- Fuel tank 395l / AD-Blue 80l
- Tires 1st & 2nd axle: 385/65 R22.5
- Tires driven axles: 315/80 R22.5
- Rims on all axles: aluminium Alcoa DuraBright
- Cabin colour: Scania Ivory White / chassis colour: Scania Sub Grey
- Cabin type: CR20N
- Premium Cabin interior



- 
- auxiliary heating: 3kW
  - Multifunctional steering wheel
  - Infotainment system equipped with 10.1-inch colour display
  - GSR II options included